

WSD 10



Water suction and delivery hose for applications in industries, building and agriculture.

TUBE	Black SBR rubber tube
REINFORCEMENT	High tensile textile reinforcement; Embedded steel wire helix.
COVER	Black special rubber cover - abrasion - heat and weather resistant; Smooth wrapped finish.
TEMPERATURE	-30° C to +70° C
MADE IN	ITALY

CODE	Inner Diameter ID		Outside Diameter OD		Working Pressure		Burst Pressure		Theoretical Weight
	mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
WSH-10-1"	25	1"	35	1 3/8"	10	145	30	435	0,700
WSH-10-1 3/16"	30	1 3/16"	41	1 5/8"	10	145	30	435	0,800
WSH-10-1 1/4"	32	1 1/4"	43	1 11/16"	10	145	30	435	0,890
WSH-10-1 3/8"	35	1 3/8"	46	1 13/16"	10	145	30	435	1,050
WSH-10-1 1/2"	38	1 1/2"	49	1 15/16"	10	145	30	435	1,200
WSH-10-1 37/64"	40	1 37/64"	51	2"	10	145	30	435	1,350
WSH-10-1 25/32"	45	1 25/32"	56	2 13/64"	10	145	30	435	1,580
WSH-10-2"	51	2"	62	2 7/16"	10	145	30	435	1,800
WSH-10-2 3/8"	60	2 3/8"	72	2 27/32"	10	145	30	435	2,200
WSH-10-2 1/2"	63,5	2 1/2"	76	3"	10	145	30	435	2,300
WSH-10-3"	76	3"	87	3 27/64"	10	145	30	435	2,900
WSH-10-3 5/32"	80	3 5/32"	92	3 5/8"	10	145	30	435	2,950
WSH-10-3 35/64"	90	3 35/64"	102	4"	10	145	30	435	3,500
WSH-10-4"	102	4"	114	4 1/2"	10	145	30	435	4,000
WSH-10-4 11/32"	110	4 11/32"	125	4 59/64"	10	145	30	435	4,800
WSH-10-5"	127	5"	142	5 5/8"	10	145	30	435	5,700
WSH-10-6"	152	6"	166	6 17/32"	10	145	30	435	7,500
WSH-10-8"	203	8"	228	9"	10	145	30	435	14,000