

R15**SAE 100R15****USE**

Multiples steel wire spiral, extra high pressure hose

FLUIDS

Mineral oils, vegetable and rape seed oils, glycol and polyglycol based oils, synthetic ester based oils, oils in aqueous emulsion, water

CONSTRUCTION

Tube consists of oil resistant synthetic rubber, multiples layers high tensile steel spiral reinforcement, and environment resistant synthetic rubber

Cont. Service Temp. Range

-40°C / +121°C

Max. Operating Temp. Range

+121°C

SAFETY FACTOR

1 : 4

BRAND

HYDROFLEX

MSHA Approved

Part No.	Dash										
		DN		O.D.		W.P.		B.P		Bend Radius	Weight
		mm	inch	mm		bar	psi	bar	psi	mm	g/m
R15-06	-6	10	3/8"	21.5		420	6090	1680	24360	150	800
R15-08	-8	12.5	1/2"	25		420	6090	1680	24360	200	1030
R15-12	-12	19	3/4"	31.5		420	6090	1680	24360	265	1630
R15-16	-16	25	1"	38		420	6090	1680	24360	330	2180
R15-20	-20	31.5	1.1/4"	48.6		420	6090	1680	24360	445	3810
R15-24	-24	38	1.1/2"	56.7		420	6090	1680	24360	530	5230